




## TZR Bearing Machine Development Co.,...



NUP307 Bearing 2D drawings and 3D CAD models

### NTN NUP307 cylindrical roller bearings

Bearing No. NUP307

Size	35x80x21 mm
Bore Diameter	35,000 mm
Outer Diameter	80,000 mm
Width	21,000 mm
d	35,000 mm
D	80,000 mm
B	21,000 mm
C	21,000 mm
Category	Cylindrical Roller Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.51
EAN	4547359135879
Product Group	B04144
Bore Profile	Straight
Cage Material	Steel
Precision Class	RBEC 1   ISO P0
Number of Rows of Rollers	Single Row
Separable	No
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C3-Loose
Retainer	Yes
Relubricatable	Yes



## TZR Bearing Machine Development Co.,...

Inch - Metric	Metric
Other Features	1 Rib Inner Ring with Side Plate   2 Rib Outer Ring   Cage On Outer Ring ID
Long Description	35MM Bore; Straight Bore Profile; 80MM Outside Diameter; 21MM Width; Steel Cage Material; RBEC 1   ISO P0; Single Row; Not Separable; No Snap Ring; Relubricatable; C3-Loose Internal Clearance; Retain
Category	Cylindrical Roller Bearing
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Manufacturer Item Number	NUP307
Weight / LBS	1.114
Bore	1.378 Inch   35 Millimeter
Outside Diameter	3.15 Inch   80 Millimeter
Width	0.827 Inch   21 Millimeter
bore diameter:	35 mm
static load capacity:	47000 N
outside diameter:	80 mm
precision rating:	ISO Class 0
overall width:	21 mm
maximum rpm:	11000 rpm
flanges:	(2) Outer Ring, (2) Inner Ring
bearing material:	Hardened Alloy Steel
bore type:	Straight
cage material:	Pressed Steel
number of rows:	1



## TZR Bearing Machine Development Co.,...

finish/coating:	Uncoated
internal clearance:	CN
closure type:	Open
ring separation:	Separable Inner Ring
fillet radius:	1.5 mm
operating temperature range:	-40 to 120 ° C
manufacturer product page:	<a href="#">Click here</a>
dynamic load capacity:	49500 N